

## Vacuum module

VEE-QCMV HV 2 07 13

Part no.: 10.01.36.00199

<https://www.schmalz.co.jp/10.01.36.00199>

Home > Vacuum Technology for Automation > Vacuum Components > Area Gripping Systems and End Effectors > Vacuum End Effectors VEE > Vacuum Modules VEE-QCMV > VEE-QCMV HV 2 07 13

### VEE vacuum module with integrated ejector module ecoPump SEP




Shape: High Vacuum

Number of stages: 2

Nozzle size: 0.7 mm

### Design Data



| Attribute | Value    |
|-----------|----------|
| B         | 55 mm    |
| d         | 6 mm     |
| D         | 25.40 mm |
| Dmk       | 46 mm    |
| G1        | G1/8"-F  |
| G2        | M4-M     |
| H         | 37.90 mm |
| H1        | 53 mm    |
| L         | 97.40 mm |
| L2        | 53.50 mm |
| LG2       | 7.60 mm  |

### Accessories

#### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Vacuum module

VEE-QCMV HV 2 07 13

Part no.: 10.01.36.00199

<https://www.schmalz.co.jp/10.01.36.00199>



**EMV 1.5 24V-DC 3/2 NC K-2P**

Part no.: 10.05.01.00288

Nominal size: 1.5 mm

Voltage DC: 24V – DC

Function: 3/2-way valve

Control valve: Normally closed

Connecting thread: M5-M

Pressure range (operating pressure): 3.5 ... 7.0 bar

Interface electrical connection: Cable, 2 pol



**FLAN-PL 55x7.5-AB1**

Part no.: 10.01.30.00015

External diameter D: 55 mm

Length L: 7.5 mm

Size: AB1



**FLAN-PL 55x7.5-EL1**

Part no.: 10.01.30.00208

External diameter D: 55 mm

Length L: 7.5 mm

Size: EL1

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Vacuum module

VEE-QCMV HV 2 07 13

Part no.: 10.01.36.00199

<https://www.schmalz.co.jp/10.01.36.00199>



### FLAN-PL 55x9.5-JP1

Part no.: 10.01.30.00194

External diameter D: 55 mm

Length L: 9.5 mm

Size: JP1

Thread G1: G3/8"-F



### FLAN-PL 63x10.5-AD1

Part no.: 10.01.30.00016

External diameter D: 63 mm

Length L: 10.5 mm

Size: AD1



### FLAN-PL 63x11.5-UNI

Part no.: 10.01.30.00017

External diameter D: 63 mm

Length L: 11.5 mm

Size: UNI

## Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Vacuum module

VEE-QCMV HV 2 07 13

Part no.: 10.01.36.00199

<https://www.schmalz.co.jp/10.01.36.00199>



### FLAN-PL 80x12-ST1

Part no.: 10.01.30.00167

External diameter D: 80 mm

Length L: 12 mm

Size: ST1



### RFBP 50 50 BA SPB2

Part no.: 10.01.45.00096

Length L: 50 mm

Width B: 50 mm

Connection: Bayonet connection

Suct. cups: Bellows suct. cup SPB2



### RFBP 100 58 BA SPB2

Part no.: 10.01.45.00091

Length L: 100 mm

Width B: 58 mm

Connection: Bayonet connection

Suct. cups: Bellows suct. cup SPB2

## Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Vacuum module

VEE-QCMV HV 2 07 13

Part no.: 10.01.36.00199

<https://www.schmalz.co.jp/10.01.36.00199>



**RFBP 100 58 BA 010**

Part no.: 10.01.45.00092

Length L: 100 mm

Width B: 58 mm

Connection: Bayonet connection

Material type: Foam 0, Height 10 mm



**RFBP 120 120 BA SPB2**

Part no.: 10.01.45.00085

Length L: 120 mm

Width B: 120 mm

Connection: Bayonet connection

Suct. cups: Bellows suct. cup SPB2



**RFBP 120 120 BA 010**

Part no.: 10.01.45.00086

Length L: 120 mm

Width B: 120 mm

Connection: Bayonet connection

Material type: Foam 0, Height 10 mm

## Spare parts

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Vacuum module

VEE-QCMV HV 2 07 13

Part no.: 10.01.36.00199

<https://www.schmalz.co.jp/10.01.36.00199>



### SEP HV 2 07 13

Part no.: 10.02.01.01394

Shape: High Vacuum

Number of stages: 2

Nozzle size: 0.7 mm

Hole diameter: 13 mm

Degree of evacuation: 85 %

Pressure range (operating pressure): 2.0 ... 6.0 bar

Pressure optimal: 4 bar

Suction rate (max.): 42.5 l/min

Air consumption suction: 23.5 l/min



### SHC 2 13

Part no.: 10.02.01.01428

Number of stages: 2

Hole diameter: 13 mm

External diameter D: 11.2 mm

Length L: 18 mm

Thread G1: M16x1-M

## Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)