

Plug union, straight

STV-GE G1/4-AG 4

Part no.: 10.08.02.00203

<https://www.schmalz.co.jp/10.08.02.00203>

Home > Screw in Push Fittings > STV-GE G1/4-AG 4

Push-in Fitting, straight



Thread G1: G1/4"-M

Hose diameter: 4 mm


Material: Brass

Operating temperature: -20 ... 80 ° C

External diameter D: 8.6 mm

Length L: 11.8 mm

Design Data



Attribute	Value
D	8.60 mm
d	4 mm
G1	G1/4"-M
dn	4 mm
L	11.80 mm
L1	19.60 mm
L2	7.30 mm
LG1	7.80 mm
SW1	17 mm

Technical Data

Attribute	Value
Hose type	Hose D = 4 d = 2
Hose type	4-2
Material	Brass
Pressure range (operating pressure)	-0.95 ... 15.00 bar
Operating temperature	-20 ... 80 ° C
Weight	15 g
Product family	STV

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp

Plug union, straight

STV-GE G1/4-AG 4

Part no.: 10.08.02.00203

<https://www.schmalz.co.jp/10.08.02.00203>

Accessories



VSL 4-2 PE BL

Part no.: 10.07.09.00013

External diameter D: 4 mm

Internal diameter d: 2 mm

Length max.: 100 m

Material hose: PE

Pressure range (operating pressure): bar

Operating temperature: ° C



VSL 4-2 PU MI-TR

Part no.: 10.07.09.00001

External diameter D: 4 mm

Internal diameter d: 2 mm

Length max.: 50 m

Material hose: PU

Bending radius min.: 20 mm

Pressure range (operating pressure): -0.95 ... 10.00 bar

Operating temperature: -40 ... 60 ° C



VSL 4-2.7 PA MI-TR

Part no.: 10.07.09.00063

External diameter D: 4 mm

Internal diameter d: 2.7 mm

Length max.: 50 m

Material hose: PA

Bending radius min.: 30 mm

Pressure range (operating pressure): -0.95 ... 20.00 bar

Operating temperature: -40 ... 90 ° C

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp