

Plug connector, T

SVB-T 4

Part no.: 10.09.02.00020

<https://www.schmalz.co.jp/10.09.02.00020>

Home > Vacuum Technology for Automation > Vacuum Components > Filters and Connections > Hoses and Connections > Screw in Push Fittings > SVB-T 4

Plug connection, T




Hose diameter: 4 mm

Material: Brass

Operating temperature: -20 ... 80 ° C

Length L: 34 mm

Design Data



Attribute	Value
d	4 mm
D1	8.60 mm
H	16.30 mm
H1	20.60 mm
L	34 mm

Technical Data

Attribute	Value
Hose type	Hose D = 4 d = 2
Hose type	4-2
Material	Brass
Pressure range (operating pressure)	-1.00 ... 15.00 bar
Operating temperature	-20 ... 80 ° C
Weight	13 g
Product family	STV

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp

Plug connector, T

SVB-T 4

Part no.: 10.09.02.00020

<https://www.schmalz.co.jp/10.09.02.00020>



Accessories



VSL 4-2 PE BL

Part no.: 10.07.09.00013

External diameter D: 4 mm

Internal diameter d: 2 mm

Length max.: 100 m

Material hose: PE

Pressure range (operating pressure): bar

Operating temperature: ° C



VSL 4-2 PU MI-TR

Part no.: 10.07.09.00001

External diameter D: 4 mm

Internal diameter d: 2 mm

Length max.: 50 m

Material hose: PU

Bending radius min.: 20 mm

Pressure range (operating pressure): -0.95 ... 10.00 bar

Operating temperature: -40 ... 60 ° C



VSL 4-2.7 PA MI-TR

Part no.: 10.07.09.00063

External diameter D: 4 mm

Internal diameter d: 2.7 mm

Length max.: 50 m

Material hose: PA

Bending radius min.: 30 mm

Pressure range (operating pressure): -0.95 ... 20.00 bar

Operating temperature: -40 ... 90 ° C

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp