

## Vacuum hose (meter)

VSL 71-60 PU-DS-AS TR

Part no.: 10.07.09.00065

<https://www.schmalz.co.jp/10.07.09.00065>

Home > Vacuum Technology for Automation > Vacuum Components > Filters and Connections > Hoses and Connections > Vacuum / Compressed Air Hoses VSL > VSL 71-60 PU-DS-AS TR

### Hose for vacuum and compressed-air systems



External diameter D: 71 mm

Internal diameter d: 60 mm

Length max.: 15 m

Material hose: PU, wire spiral, antistatic

Bending radius min.: 156 mm

Pressure range (operating pressure): -1.00 ... 2.92 bar

Operating temperature: -40 ... 90 °C

### Design Data



| Attribute | Value |
|-----------|-------|
| d         | 60 mm |
| D         | 71 mm |

### Technical Data

| Attribute                           | Value                       |
|-------------------------------------|-----------------------------|
| Hose type                           | 71-60                       |
| Pressure range (operating pressure) | -1.00 ... 2.92 bar          |
| Operating temperature               | -40 ... 90 °C               |
| Bending radius min.                 | 156 mm                      |
| Length max.                         | 15 m                        |
| Weight/Meter                        | 1180 g/m                    |
| Weight/Meter                        | 1.18 kg/m                   |
| Material hose                       | PU, wire spiral, antistatic |

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Vacuum hose (meter)

VSL 71-60 PU-DS-AS TR

Part no.: 10.07.09.00065

<https://www.schmalz.co.jp/10.07.09.00065>

Product family

VSL

Note: Operating pressure: In reference to media and ambient temperature of + 20 ° C Min. bending radius: Referred to the inner side of the hose bend in a static state Max. length: Please indicate the tube length when placing the order!

## Accessories



SSD 65-70 ST-VZ

Part no.: 10.07.10.00098

Clamping range: 65.0 ... 70.0 mm

Material: Steel

Surface: galvanised

## Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)