

## Magnetic gripper

SGM-S 40 G1/4-IG PNP

Part no.: 10.01.17.00201

<https://www.schmalz.co.jp/10.01.17.00201>

Home > Vacuum Technology for Automation > Vacuum Components > Special Grippers > Magnetic Grippers > Magnetic Grippers  
SGM > SGM-S 40 G1/4-IG PNP

### Magnetic gripper for handling metal sheets with holes



Size: 40

Socket: G1/4"-F


Holding force max. friction ring: 100 N

Pressure range (operating pressure): 3.5 ... 6.0 bar

Add. function: Sensor PNP

Electrical connection: Male connect M12, 4 pol

### Design Data



| Attribute | Value    |
|-----------|----------|
| B         | 40.65 mm |
| D         | 40 mm    |
| d         | 26 mm    |
| G1        | G1/4"-F  |
| G2        | G1/8"-F  |
| G3        | M12x1-M  |
| G4        | M4-F     |
| H         | 70.20 mm |
| LG1       | 11 mm    |
| LG2       | 6 mm     |
| LG4       | 7 mm     |
| Lk        | 300 mm   |
| X1        | 46 mm    |
| Y1        | 12 mm    |

### Technical Data

| Attribute                           | Value           |
|-------------------------------------|-----------------|
| Holding force max. friction ring    | 100 N           |
| Remaining force                     | 0.30 N          |
| Pressure range (operating pressure) | 3.5 ... 6.0 bar |
| Installation position               | BEL             |

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Magnetic gripper

SGM-S 40 G1/4-IG PNP

Part no.: 10.01.17.00201

<https://www.schmalz.co.jp/10.01.17.00201>

|                       |              |
|-----------------------|--------------|
| Control valve         | Bistable     |
| Operating temperature | 5 ... 70 ° C |
| Weight                | 255 g        |
| Product family        | SGM          |

Note: Holding force: The value given is a statistical value with no safety factor; based on a plate with a thickness of 2 mm. For system configurations with magnetic grippers SGM, a safety factor of S = 3 must be applied

### Accessories



#### HTS-A2 SGM 30/40 OP

Part no.: 10.01.17.00581

Connection 1: Bolt with slot Ø19mm

Construction use: Magnetic gripper

Size: 30/40



#### HTS-A3 SGM 30/40 OP

Part no.: 10.01.17.00558

Connection 1: Ball head 28.5 mm

Construction use: Magnetic gripper

Size: 30/40

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Magnetic gripper

SGM-S 40 G1/4-IG PNP

Part no.: 10.01.17.00201

<https://www.schmalz.co.jp/10.01.17.00201>



**HTS-A2 D SGM 30/40 OP**

Part no.: 10.01.17.00586

Connection 1: Bolt with slot Ø19mm

Construction use: Magnetic gripper

Size: 30/40

Shape: Double block



**HTS-A3 D SGM 30/40 OP**

Part no.: 10.01.17.00582

Connection 1: Ball head 28.5 mm

Construction use: Magnetic gripper

Size: 30/40

Shape: Double block



**HPS-SGM 2M6 30/40 OP**

Part no.: 10.01.17.00655

Construction use: Magnetic gripper

Connection 1: 2x screws M6

Size: 30/40

Shape: One-piece

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Magnetic gripper

SGM-S 40 G1/4-IG PNP

Part no.: 10.01.17.00201

<https://www.schmalz.co.jp/10.01.17.00201>



**ASK B-M12-5 5000 K-5P**

Part no.: 21.04.05.00080

Electrical connection: Fem connect M12, 5 pol

Cable length: 5,000 mm

Material hose: PUR cable



**STV-GE G1/8-AG 6**

Part no.: 10.08.02.00204

Thread G1: G1/8"-M

Hose diameter: 6 mm

Material: Brass

Operating temperature: -20 ... 80 ° C

External diameter D: 11.4 mm

Length L: 16.4 mm



**STV-W G1/8-AG 6**

Part no.: 10.08.02.00158

Thread G1: G1/8"-M

Hose diameter: 6 mm

Material: Nickel plated

Operating temperature: -20 ... 80 ° C

Length L: 20.1 mm

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Magnetic gripper

SGM-S 40 G1/4-IG PNP

Part no.: 10.01.17.00201

<https://www.schmalz.co.jp/10.01.17.00201>



### VSL 6-4 PU MI-TR

Part no.: 10.07.09.00002

External diameter D: 6 mm

Internal diameter d: 4 mm

Length max.: 500 m

Material hose: PU

Bending radius min.: 35 mm

Pressure range (operating pressure): -0.95 ... 10.00 bar

Operating temperature: -20 ... 90 ° C

## Spare parts



### REIB-RING SGM 40 PU-55

Part no.: 10.01.17.00137

Construction use: Magnetic gripper

Size: 40

External diameter D: 40 mm

Internal diameter d: 26 mm



### NAEH-SCHA SMAGN-PNP S051

Part no.: 10.01.17.00199

Construction shape vacuum switch: Magn. cylind. sensor - PNP

Voltage DC: 15-30V DC

Electrical connection: Male connect M12, 4 pol

## Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)