

Compact ejector

SEM-C 50 SDA NO AS

Part no.: 10.02.02.02966

<https://www.schmalz.co.jp/10.02.02.02966>

Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Generators > Compact Ejectors > Compact Ejectors
SEM-C > SEM-C 50 SDA NO AS

Multi-stage ejector (controllable) with high suction capacity



Size: 50

Add. function: Axial silencer

Suction rate (max.): 554 l/min


Air consumption suction: 190 l/min

Max. vacuum: -850 mbar

Control valve: Normally open

construction shape compact ejectors: With blow-off system

Datos de diseño



Atributo	Valor
B	94.50 mm
B1	210 mm
d	5.50 mm
D1	50 mm
G1	G1/4"-F
G2	G3/4"-F
G3	G3/4"-F
H	80 mm
L	219.50 mm
L1	339.50 mm
L2	10.50 mm
X1	183 mm
Y1	55 mm

Datos técnicos

Atributo	Valor
Suction rate (max.)	554 l/min
Degree of evacuation	86 %
Air consumption suction	190 l/min
Control valve	Normally open

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp

Compact ejector

SEM-C 50 SDA NO AS


Part no.: 10.02.02.02966

<https://www.schmalz.co.jp/10.02.02.02966>

Weight	1.92 kg
Operating temperature	0 ... 50 ° C
Size	50
Product family	SEM-C

Note: Air consumption: At optimal operating pressure Hose diameter: For max. length 2 m

Accesorios



ASK B-Form-C 5000 K-3P

N° de artículo.: 21.04.06.00084

Electrical connection: Fem connect Form C

Cable length: 5,000 mm

Material hose: PVC cable

Piezas de repuesto



SD G3/4-AG 50x120 SEM

N° de artículo.: 10.02.01.00312

Thread G1: G3/4"-M

External diameter D: 50 mm

Length L: 120 mm

Construction use: Multi-stage ejectors