

Bellows suction cup (round)

FG 18 NBR-55 N016

Part no.: 10.01.06.00053

<https://www.schmalz.co.jp/10.01.06.00053>

Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Bellows Suction Cups (Round) > FG 18 NBR-55 N016

Bellows suction cup (round) for very uneven workpieces




Size: 18

Suction cup material: Nitrile rubber NBR

Material hardness [Shore A]: 55 Shore A

Number of folds: 2.5

Design Data



Attribute	Value
d	4.50 mm
d2	8 mm
D1	17.80 mm
Dk	10 mm
Dmax (S)	19 mm
Ds	17.20 mm
H	22.60 mm
H2	3.80 mm
H3	9 mm
Z (Stroke)	9 mm

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

Technical Data

Attribute	Value
Suction force (-600mbar)	3.02 N
Pull-off force	8.50 N
Volume	1.65 cm ³
Curve radius (min) (convex)	20 mm
Size	18
Nipple family	N 016
Number of folds	2.50

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp

Bellows suction cup (round)

FG 18 NBR-55 N016

Part no.: 10.01.06.00053

<https://www.schmalz.co.jp/10.01.06.00053>

Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	55 Shore A
Weight	1.90 g
Product family	FG

Accessories



SA-NIP N016 G1/8-AG DN350

Part no.: 10.01.06.05735

Nipple family: N 016
Thread G1: G1/8"-M
Length L1: 20 mm
Fitting length: 6 mm
Nominal diameter dn: 3.5 mm
Material: Aluminum



SA-NIP N016 G1/8-IG DN350

Part no.: 10.01.06.05731

Nipple family: N 016
Thread G1: G1/8"-F
Length L1: 18.5 mm
Fitting length: 12 mm
Nominal diameter dn: 3.5 mm
Material: Aluminum

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp

Bellows suction cup (round)

FG 18 NBR-55 N016

Part no.: 10.01.06.00053

<https://www.schmalz.co.jp/10.01.06.00053>



SA-NIP N016 M5-AG DN250

Part no.: 10.01.06.00123

Nipple family: N 016

Thread G1: M5-M

Length L1: 16 mm

Fitting length: 5 mm

Nominal diameter dn: 2.5 mm

Material: Aluminum

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp