

## Bellows suction cups (round)

FSGA 11 NBR-ESD-55 M5-AG

Part no.: 10.01.06.04319

<https://www.schmalz.co.jp/10.01.06.04319>

Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Bellows Suction Cups (Round) > Bellows Suction Cups FSGA (1.5 Folds) > FSGA 11 NBR-ESD-55 M5-AG

### Bellows suction cup (round) with optimal adaptation to uneven surfaces



Size: 11

Suction cup material: Nitrile rubber NBR-ESD

Material hardness [Shore A]: 55 Shore A


Nipple material: Aluminum

Connection: M5-M

Number of folds: 1.5

Vacuum connection: M5-M

### Design Data



| Attribute  | Value    |
|------------|----------|
| d2         | 5.10 mm  |
| Dmax (S)   | 13 mm    |
| dn         | 2.50 mm  |
| Ds         | 10.40 mm |
| G1         | M5-M     |
| H          | 21 mm    |
| LG1        | 5 mm     |
| SW1        | 7 mm     |
| Z (Stroke) | 4 mm     |

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

### Technical Data

| Attribute                   | Value                  |
|-----------------------------|------------------------|
| Suction cup material        | Nitrile rubber NBR-ESD |
| Material hardness [Shore A] | 55 Shore A             |
| Size                        | 11                     |
| Number of folds             | 1.50                   |
| Connection                  | M5-AG                  |
| Curve radius (min) (convex) | 10 mm                  |
| Volume                      | 0.23 cm <sup>3</sup>   |

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)

## Bellows suction cups (round)

FSGA 11 NBR-ESD-55 M5-AG

Part no.: 10.01.06.04319

<https://www.schmalz.co.jp/10.01.06.04319>

|                          |        |
|--------------------------|--------|
| Suction force (-600mbar) | 0.95 N |
| Pull-off force           | 3.80 N |
| Hose diameter (rec.) d   | 2 mm   |
| Weight                   | 2 g    |
| Product family           | FSGA   |

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface – they do not include a safety factor Pull-off force: The pull-off force of the versions made of natural rubber is reduced by about 40% Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m

### Spare parts



**FGA 11 NBR-ESD-55 N062**

Part no.: 10.01.06.04136

Size: 11

Suction cup material: Nitrile rubber NBR-ESD

Material hardness [Shore A]: 55 Shore A

Number of folds: 1.5



**SA-NIP N062 M5-AG DN250**

Part no.: 10.01.06.05668

Thread G1: M5-M

Length L1: 15.9 mm

Fitting length: 5 mm

Nominal diameter dn: 2.5 mm

Material: Aluminum

### Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | [schmalz@schmalz.co.jp](mailto:schmalz@schmalz.co.jp)