

Bellows suction cup (round)

SAB 60 NBR-60 G1/4-AG

Part no.: 10.01.06.00805

<https://www.schmalz.co.jp/10.01.06.00805>

Home > Bellows Suction Cups SAB (1.5 Folds) > SAB 60 NBR-60 G1/4-AG

Bellows suction cup (round) for very dynamic handling of smooth and oily workpieces



Size: 60

Suction cup material: Nitrile rubber NBR


Material hardness [Shore A]: 60 Shore A

Nipple material: Aluminum

Connection: G1/4-AG

Number of folds: 1.5

Design Data



Attribute	Value
dn	6 mm
D1	48 mm
Dmax (S)	67 mm
Ds	61.10 mm
G1	G1/4"-M
H	41.30 mm
LG1	10 mm
SW1	22 mm
Z (Stroke)	14.50 mm

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

Technical Data

Attribute	Value
Suction force (-600mbar)	82 N
Pull-off force	130 N
Lateral force	145 N
Lateral force (oily surface)	77 N
Volume	28.80 cm ³
Curve radius (min) (convex)	65 mm
Hose diameter (rec.) d	6 mm
Size	60

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp

Bellows suction cup (round)

SAB 60 NBR-60 G1/4-AG

Part no.: 10.01.06.00805

<https://www.schmalz.co.jp/10.01.06.00805>

Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	60 Shore A
Weight	49.10 g
Product family	SAB
Number of folds	1.50

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Lateral force: The specified lateral forces are values measured at a vacuum of -0.6 bar with a dry or oily, smooth, flat workpiece surface. Depending on the workpiece surface and its quality, the actual values may deviate from these values Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m