

Suction plate (round)

SPL-HT 190 FPM-F-65 G1/2-AG

Part no.: 10.01.01.00832

<https://www.schmalz.co.jp/10.01.01.00832>

Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Suction Cups for High-Temperature Applications > Suction Plates for High-Temperature SPL-HT FPM-F > SPL-HT 190 FPM-F-65 G1/2-AG

Suction plate for high-temperature applications



Size: 190


Suction cup material: Fluorocautchuc FPM-F

Material hardness [Shore A]: 65 Shore A

Connection: G1/2-AG

Working temperature max.: 350 ° C

Design Data



Attribute	Value
dn	10 mm
Dmax (S)	209 mm
Ds	190 mm
G1	G1/2"-M
H	66 mm
LG1	18 mm
SW1	32 mm
Z (Stroke)	8 mm

Technical Data

Attribute	Value
Suction force (-600mbar)	1050 N
Volume	165 cm ³
Curve radius (min) (convex)	350 mm
Evacuation rate for pu = -0,6 bar	30 l/min
Size	190
Number of folds	0
Working temperature max.	350 ° C
Suction cup material	Fluorocautchuc FPM-F

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp

Suction plate (round)

SPL-HT 190 FPM-F-65 G1/2-AG

Part no. : 10.01.01.00832

<https://www.schmalz.co.jp/10.01.01.00832>

Weight	1420 g
Product family	SPL-HT

Spare parts



SPL-HT 190 FPM-F-65

Part no. : 10.01.01.00834

Size: 190

Suction cup material: Fluorocautchuc FPM-F

Material hardness [Shore A]: 65 Shore A

Working temperature max. : 350 ° C



SPL-HT 190 FPM-F-65

Part no. : 10.01.01.00834

Size: 190

Suction cup material: Fluorocautchuc FPM-F

Material hardness [Shore A]: 65 Shore A

Working temperature max. : 350 ° C

Contact Schmalz

Schmalz K.K. | 3001-7 Odana-cho, Tsuzuki-ku, 224-0027 Yokohama, Japan | +81 45 565 5150 | schmalz@schmalz.co.jp